

SEA&LAND ELECTRONIC CORP.
 13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: R16-700
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER: A
 REV DATE: 2014/10/14
 PAGE NO.: 1 of 1

Specification Sheet

Insulating Material:
 Meets UL94 V-0 Requirements

Lead-Free, RoHS Compliant

Lead Material:
 Tin Plated Copper, 20 AWG (0.81mm/0.032" Dia.)

Marking:

┌── Sea&Land Logo

└

R16 - Radial Type 16V

700 - Hold Current

XXXXY- Date Code & Factory Code




TABLE I. DIMENSIONS:

	A	B	C	D	E
	Max.	Max.	Typ.	Min.	Max.
mm	13.00	17.20	5.10	7.60	3.1

TABLE II. PERFORMANCE RATINGS:

Model Number	V_{max} (Vdc)	I_{max} (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	P_d Max. (W)	Maximum Time To Trip		Resistance	
						Current (A)	Time (Sec)	Ri min (Ω)	R1 max (Ω)
R16-700	16	100	7.00	11.90	3.00	21.00	10.0	0.008	0.019

Order Information

Packing

R16	700	Model	Bag Q'ty
Radial type Vmax=16 V	Hold Current 7.00(A)	R16-700	500

Recognition:



E319079(Sea&Land)