

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: SL1812400
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER:
 REV DATE: 2025-2-20
 PAGE NO.: 1 of 1

Specification Sheet

Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

Alpha Logo
 Part Identification




TABLE I. DIMENSIONS:

| Model | A | | B | | C | | D | E |
|-----------|------|------|------|------|------|------|------|------|
| | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Min. |
| SL1812400 | 4.37 | 4.73 | 3.07 | 3.41 | 0.40 | 0.80 | 0.30 | 0.15 |

Unit:mm

TABLE II. PERFORMANCE RATINGS:

| Model | Marking | V_{max} (V) | I_{max} (A) | I_{hold} @25°C (A) | I_{trip} @25°C (A) | P_d Typ. (W) | Maximum Time To Trip | | Resistance | |
|-----------|---------|------------------|------------------|----------------------------|----------------------------|----------------------|----------------------|---------------|----------------------|----------------------|
| | | | | | | | Current (A) | Time (Sec) | $R_{i_{min}}$ (Ω) | $R_{1_{max}}$ (Ω) |
| SL1812400 | SL400 | 6 | 50 | 4.00 | 8.00 | 1.5 | 20.0 | 5.0 | 0.0040 | 0.0140 |

Order Information

Packaging

| SL1812 | 400 | Tape & Reel Quantity |
|--------------------------|-----------------|----------------------|
| Product name | Hold Max | 1500 pcs/reel |
| Size 4532 mm /1812 mils | Current voltage | |
| SL: surface mount device | 4.00A | |

Recognition:

2015/863/EU

EN14582

