

**SEA&LAND ELECTRONIC CORP.**  
 13F., No.120-10,  
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,  
 Taiwan  
 Tel.: 886-2-8221-2567  
 Fax.: 886-2-2225-7268

**Techfuse**  
**PTC Devices**  
 Resettable Fuse

PRODUCT: SL1210550-8V  
 DOCUMENT: QR0429  
 ECN. NO.:  
 REV LETTER:  
 REV DATE: 2023-7-14  
 PAGE NO.: 1 of 1

## Specification Sheet

Terminal Pad Solderability:  
 Meets EIA Specification RS186-9E  
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:  
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

Part Identification




TABLE I. DIMENSIONS:

Model	Marking	A		B		C		D	D
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.
SL1210550-8V		3.00	3.50	2.35	2.90	0.50	1.00	0.30	0.10

Unit:mm

TABLE II. PERFORMANCE RATINGS:

Model	Marking	$V_{max}$ (V)	$I_{max}$ (A)	$I_{hold}$ @25°C (A)	$I_{trip}$ @25°C (A)	$P_d$ Typ. (W)	Maximum Time To Trip		Resistance	
							Current (A)	Time (Sec)	$R_{i_{min}}$ (Ω)	$R_{1_{max}}$ (Ω)
SL1210550-8V		8	50	5.50	11.00	1.5	20.0	5.0	0.0008	0.0100

### Order Information

### Packaging

SL1210	550-8V	Tape & Reel Quantity
Product name	Hold	Max
Size 3225 mm / 1210 mils	Current	voltage
SL: surface mount device	5.50A	4000 pcs/reel

Recognition:

E201504/E319079



2015/863/EU



EN14582

