

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: SMD0805-035
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER:
 REV DATE: 2013-4-2
 PAGE NO.: 1 of 1

Specification Sheet


Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

Part Identification
 3 = 035

**TABLE I. DIMENSIONS:**

Model	Marking	A		B		C		D	E
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.
SMD0805-035	3	2.00	2.20	1.20	1.50	0.50	1.00	0.20	0.10

Unit:mm

TABLE II. PERFORMANCE RATINGS:

Model	Marking	V_{max} (Vdc)	I_{max} (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	P_d Typ. (W)	Maximum Time To Trip		Resistance	
							Current	Time	$R_{i_{min}}$	$R_{1_{max}}$
							(A)	(Sec)	(Ω)	(Ω)
SMD0805-035	3	6.0	100	0.35	0.75	0.50	8.0	0.10	0.250	1.200

Order Information**Packaging**

SMD0805	035	Tape & Reel Quantity
Product name	Hold Max	5,000 pcs/reel
Size 2012 mm / 0805 mils	Current voltage	
SMD: surface mount device	0.35A	

Recognition: UL Approved.

E201504/E319079

