

**SEA&LAND ELECTRONIC CORP.**

13F.,No.120-10,  
 Sec.3,Zhongshan Rd.,Zhonghe City,Taipei County,  
 Taiwan, R.O.C.  
 Tel.: 886-2-8221-2567  
 Fax.: 886-2-2225-7268

**Techfuse**  
**PTC Devices**  
 Resettable Fuse

PRODUCT: C250-200  
 DOCUMENT: QR0429  
 ECN. NO.:  
 REV LETTER:  
 REV DATE: 2015/11/10  
 PAGE NO.: 1 of 1

# Specification Sheet

Max Interrupt Voltage: 250 Vac  
 Max Operating Voltage: 60 Vdc  
 Maximum Interrupt Current: 10 A

Insulating Material:  
 meets UL94 V-0 Requirements


Lead-free, RoHS compliant

Lead Material:  
 Tin plated copper, 0.6 Dia.

Marking:

└── Sea&Land Logo  
 ↑

C250 - Vmax 250V  
 200 - hold current  
 XXX - Date code



**TABLE I. DIMENSIONS:**

	A	B	C	D
	MAX	MAX	TYP	Max
mm	10.5	13.5	5.1	4.6

**TABLE II. PERFORMANCE RATINGS:**

Model	V <sub>max</sub> (Vac)	I <sub>max</sub> (A)	I <sub>hold</sub> @25°C (A)	Maximum Time To Trip		Resistance	
				Current (A)	Time (Sec)	Ri min (Ω)	Ri max (Ω)
C250-200	250	10	0.20	1.00	15.0	3.00	6.00

Order Information

Packing

C250	200	Model	Bag Q`ty
Product name	Hold Current	C250-200	1000
250V	mA		

Recognition: UL Approved

E319079

