

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan

Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: R16-1400
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER: A
 REV DATE: 2014/12/31
 PAGE NO.: 1 of 1

Specification Sheet

Insulating Material:
 Meets UL94 V-0 Requirements

Lead-Free, RoHS Compliant

Lead Material:
 Tin Plated Copper, 18 AWG (1.0mm/0.04" Dia.)

Marking:

- └── Sea&Land Logo
- ⌞
- R16 - Radial Type 16V
- 1400 - Hold Current
- XXXXY- Date Code & Factory Code




TABLE I. DIMENSIONS:

	A	B	C	D	E
	Max.	Max.	Typ.	Min.	Max.
mm	20.50	28.00	10.20	7.60	3.5

TABLE II. PERFORMANCE RATINGS:

Model Number	V_{max} (Vdc)	I_{max} (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	P_d Max. (W)	Maximum Time To Trip		Resistance	
						Current (A)	Time (Sec)	Ri min (Ω)	R1 max (Ω)
R16-1400	16	100	14.00	23.80	4.60	42.00	30.0	0.0020	0.008

Order Information

Packing

R16	1400	Model	Bag Q'ty
Radial type Vmax=16 V	Hold Current 14.00(A)	R16-1400	200

Recognition:



E319079(Sea&Land)