

**SEA&LAND ELECTRONIC CORP.**

13F., No.120-10,  
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,  
 Taiwan  
 Tel.: 886-2-8221-2567  
 Fax.: 886-2-2225-7268

**Techfuse**  
**PTC Devices**  
 Resettable Fuse

PRODUCT: SL0805-125  
 DOCUMENT: QR0429  
 ECN. NO.:  
 REV LETTER: A  
 REV DATE: 2021-9-18  
 PAGE NO.: 1 of 1


# Specification Sheet

Terminal Pad Solderability:  
 Meets EIA Specification RS186-9E  
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:  
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:  
 Part Identification

**TABLE I. DIMENSIONS:**

Model	A	B	C	D	E
	Max.	Max.	Max.	Min.	Min.
SL0805-125	2.50	1.80	0.80	0.20	0.10

Unit:mm

**TABLE II. PERFORMANCE RATINGS:**

Model	$V_{max}$ (Vdc)	$I_{max}$ (A)	$I_{hold}$ @25°C (A)	$I_{trip}$ @25°C (A)	$P_d$ Typ. (W)	Maximum Time To Trip		Resistance	
						Current (A)	Time (Sec)	$R_{i_{min}}$ (Ω)	$R_{1_{max}}$ (Ω)
						SL0805-125	6.0	50	1.25

**Order Information****Packaging**

SL0805-125	125	Tape & Reel Quantity	
Product name	Hold	Max	4,000 pcs/reel
Size 2012 mm / 0805 mils	Current	voltage	
SMD: surface mount device	1.25A		

Agency Approvals:

Regulation/Standard:  **2015/863/EU**

 **EN14582**