

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: SMD100L
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER:
 REV DATE: 2024-8-10
 PAGE NO.: 1 of 1

Specification Sheet

Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

α Alpha Logo
 100L Part Identification




TABLE I. DIMENSIONS:

Model	A		B		C		D
	MIN	MAX	MIN	MAX	MIN	MAX	MIN
SMD100L	6.73	7.98	4.80	5.44	0.40	1.00	0.30

Unit:mm

TABLE II. PERFORMANCE RATINGS:

Model	V_{max} (V)	I_{max} (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	P_d Typ. (W)	Maximum Time To Trip		Resistance	
						Current (A)	Time (Sec)	$R_{i_{min}}$ (Ω)	$R_{1_{max}}$ (Ω)
SMD100L	33	100	1.10	2.20	1.500	8.0	0.5	0.065	0.410

Order Information

Packaging

SMD2920	100	Tape & Reel Quantity
Product name	Hold	Max
Size 7555 mm / 2920 mils	Current	voltage
SMD: surface mount device	1.10A	2000 pcs/reel

Recognition:

E201504/E319079
 2015/863/EU
 EN14582

