

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: SMD0805-003-60V
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER: A
 REV DATE: 2023-1-3
 PAGE NO.: 1 of 1

Specification Sheet


Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

Part Identification
 T = 003

**TABLE I. DIMENSIONS:**

| Model | Marking | A | | B | | C | | D | E |
|-----------------|---------|------|------|------|------|------|------|------|------|
| | | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Min. |
| SMD0805-003-60V | T | 1.90 | 2.20 | 1.20 | 1.50 | 0.60 | 1.30 | 0.20 | 0.10 |

Unit:mm

TABLE II. PERFORMANCE RATINGS:

| Model | Marking | V_{max} (Vdc) | I_{max} (A) | I_{hold} @25°C (A) | I_{trip} @25°C (A) | P_d Typ. (W) | Maximum Time To Trip | | Resistance | |
|-----------------|---------|--------------------|------------------|----------------------------|----------------------------|----------------------|-------------------------|---------------|----------------------|----------------------|
| | | | | | | | Current (A) | Time (Sec) | $R_{i_{min}}$ (Ω) | $R_{1_{max}}$ (Ω) |
| SMD0805-003-60V | T | 60 | 40 | 0.03 | 0.10 | 0.5 | 0.2 | 1.00 | 6.000 | 50.000 |

Order Information**Packaging**

| SMD0805 | 003-60V | Tape & Reel Quantity | |
|---------------------------|---------|----------------------|----------------|
| Product name | Hold | Max | 5,000 pcs/reel |
| Size 2012 mm / 0805 mils | Current | voltage | |
| SMD: surface mount device | 0.03A | | |

Recognition:

2015/863/EU 
 EN14582 