

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: SL1812250
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER:
 REV DATE: 2025-2-20
 PAGE NO.: 1 of 1

Specification Sheet

Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

Alpha Logo
 Part Identification




TABLE I. DIMENSIONS:

Model	A		B		C		D	E
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.
SL1812250	4.37	4.73	3.07	3.41	0.40	0.70	0.30	0.15

Unit:mm

TABLE II. PERFORMANCE RATINGS:

Model	Marking	V_{max} (V)	I_{max} (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	P_d Typ. (W)	Maximum Time To Trip		Resistance	
							Current (A)	Time (Sec)	$R_{i_{min}}$ (Ω)	$R_{1_{max}}$ (Ω)
SL1812250	SL260	6	50	2.50	6.00	1.0	13.0	2.0	0.0040	0.0200

Order Information

Packaging

SL1812	250	Tape & Reel Quantity
Product name	Hold Max	1500 pcs/reel
Size 4532 mm /1812 mils	Current voltage	
SL: surface mount device	2.50A	

Recognition:

2015/863/EU

EN14582

