

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist.,New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: mSMD050-15V
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER:
 REV DATE: 2021-3-9
 PAGE NO.: 1 of 1

Specification Sheet

Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

α Alpha Logo
 050 Part Identification




TABLE I. DIMENSIONS:

Model	A		B		C		D	E
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.
mSMD050-15V	4.37	4.73	3.07	3.41	0.40	0.90	0.30	0.25

Unit:mm

TABLE II. PERFORMANCE RATINGS:

Model	V_{max} (V)	I_{max} (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	P_d Typ. (W)	Maximum Time To Trip		Resistance	
						Current (A)	Time (Sec)	$R_{i_{min}}$ (Ω)	$R_{1_{max}}$ (Ω)
mSMD050-15V	15.0	100	0.50	1.00	0.8	8.0	0.15	0.150	1.000

mSMD1812	050-15V	Tape & Reel Quantity
Product name	Hold	Max
Size 4532 mm / 1812 mils	Current	voltage
SMD: surface mount device	0.50A	1500 pcs/reel

Recognition: UL/TUV, approved. E201504/E319079
 R 50481056
 2015/863/EU
 EN14582

