

Specification Sheet

Terminal Pad Solderability:
Meets EIA Specification RS186-9E
And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:
Part Identification




TABLE I. DIMENSIONS:

Model	Marking	A		B		C		D	E
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.
SL0805110		1.9	2.5	1.2	1.8	0.4	0.8	0.2	0.1

Unit:mm

TABLE II. PERFORMANCE RATINGS:

Model	Marking	V _{max} (Vdc)	I _{max} (A)	I _{hold} @25°C (A)	I _{trip} @25°C (A)	P _d Typ. (W)	Maximum Time To Trip		Resistance	
							Current (A)	Time (Sec)	R _{i_min} (Ω)	R _{1_max} (Ω)
SL0805110		6	50	1.1	3.0	1.0	8.0	0.5	0.008	0.120

Order Information

Packaging

SL0805		110	Tape & Reel Quantity
Product name		Hold	4,000 pcs/reel
Size 2012 mm / 0805 mils		Current	
SL: surface mount device		1.10A	

Recognition:

UL Pending.

E201504/E319079



2015/863/EU

 RoHS

EN14582

