

SEA&LAND ELECTRONIC CORP.
 13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: SMD1210-020-60V
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER:
 REV DATE: 2026/3/27
 PAGE NO.: 1 of 1


Specification Sheet

Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:
 Part Identification
 SMD1210-020 = αC



| Model | Marking | A | | B | | C | | D | E |
|-----------------|------------|------|------|------|------|------|------|------|------|
| | | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Min. |
| SMD1210-020-60V | αC | 3.00 | 3.43 | 2.35 | 2.80 | 0.40 | 0.90 | 0.30 | 0.10 |

Unit:mm

TABLE II. PERFORMANCE RATINGS:

| Model | Marking | V_{max} (V) | I_{max} (A) | I_{hold} @25°C (A) | I_{trip} @25 (A) | P_d Typ. (W) | Maximum Time To Trip | | Resistance | |
|-----------------|------------|------------------|------------------|----------------------------|--------------------------|----------------------|-------------------------|---------------|----------------------|----------------------|
| | | | | | | | Current (A) | Time (Sec) | $R_{i_{min}}$ (Ω) | $R_{1_{max}}$ (Ω) |
| SMD1210-020-60V | αC | 60 | 100 | 0.20 | 0.40 | 0.6 | 8.0 | 0.02 | 0.400 | 5.000 |

Order Information

Packaging

| SMD1210 | 020-60V | Tape & Reel Quantity |
|---------------------------|-----------------|----------------------|
| Product name | Hold Max | 4500 pcs/reel |
| Size 3225 mm / 1210 mils | Current voltage | |
| SMD: surface mount device | 0.20A | |

Agency Approvals :



E201504(Alpha-Top)/E319079(Sea&Land)



CQC25001473187

GB 4943.1-2022; IEC 60730-1 : 2013 15、17、J.15、J.17; GB/T 7153-2002

Regulation/Standard:



2015/863/EU



EN14582